

BECO filter cartridges for food and beverage applications



Powering Business Worldwide

Wide range of filter cartridges offer complete filtration solutions for food and beverage applications

Eaton provides high-quality wrapped and pleated depth filter and membrane filter cartridges.

The BECO® filter cartridge selection offers a wide range of solutions for applications in the food and beverage industry from clarifying and fine filtration with depth filter cartridges (BECO PROTECT®) to the reduction of microorganisms and microbiological stabilisation with membrane filter cartridges (BECO MEMBRANE).

To extend service life and efficiently protect downstream membranes, Eaton can recommend the optimal combination of pre-filter and membrane filter cartridges.

BECO filter cartridges feature a variety of retention ratings, between 0.2 and 150 µm, suitable for an array of liquid filtration applications. In addition to sizes ranging from 10" (25 cm) to 40" (100 cm) and various adapter codes, filter cartridges are available with different filter material. All BECO MEMBRANE filter cartridges are testable for integrity and therefore offer high process reliability for the user.

The product range contains numerous housings and system solutions for the use of depth filter and membrane filter cartridges, such as the BECO INTEGRA® CART stainless steel filter cartridge housings and complex, automatic StepFlow® filtration systems.

Eaton filter cartridges meet national and international quality standards, such as the LFGB standard (German Food, Commodity and Feed Act) in Germany and FDA guidelines (Food and Drug Administration) from the USA. The plastic components meet European Directive (EU) 10/2011.



BECO Filter Cartridges

Selection guide

DEPTH FILTER CARTRIDGES



BECO PROTECT PG

Consist of up to 24 wrapped polypropylene fleeces that are graded from coarse to fine. The funnel design ensures that a wide particle spectrum can be absorbed, with a high retention rating and excellent backwashing capability.



BECO PROTECT CS Cellstream

An innovative wrapped cartridge using adapted BECOPAD® depth filter sheet material. This filter cartridge effectively reduces turbidity, fine colloids and bacteria while offering excellent backflush capabilities.



BECO PROTECT FS FineStream

Specially pleated polypropylene fleeces with a larger filter surface area and good depth effect. The variable flow rate from inside to outside results in minimal product loss during emptying. Self-supporting pleats ensure excellent backflush capabilities.



BECO PROTECT PP Pure

Consist of pleated polypropylene filter material, featuring a high efficiency of retention and a large filter area for high flow rates.

MEMBRANE FILTER CARTRIDGES



BECO MEMBRAN PS Beer

Specifically designed for the final filtration of beer, with a particular focus on long service life and safe retention of microorganisms. Available in retention ratings of 0.45 and 0.65 µm.



BECO MEMBRAN PS Wine

Membrane filter cartridges in 0.45 and 0.65 µm for the final filtration of wine and sparkling wine. They offer long service life and a combination of high microbiological retention with full maintenance of valuable flavor and color for the production of premium wines.



BECO MEMBRAN PS Aqua

Special polyethersulfone membrane filter cartridges with a retention rate of 0.2 µm offer high flow rates and long service life for the filtration of drinking water.



BECO MEMBRAN PS Pure

Pleated membrane filter cartridges constructed from special asymmetrical polyethersulfone (PES) material. With a wide range of retention rates from 0.2 to 1.0 µm, these filter cartridges generally meet all requirements for the final filtration of food and beverages.

FILTER CARTRIDGES FOR SERVICE MEDIA



BECO MEMBRAN PFplus

Pleated membrane filter cartridges constructed of symmetric polyvinylidene fluoride (PVDF). This membrane filter cartridge provides excellent microbiological retention and extended service life due to its excellent mechanical and thermal stability.



BECO PROTECT PB depth filter cartridges

Manufactured from thermally bonded, melt-blown polypropylene filter material with high chemical resistance. The mechanical stability of this cartridge is so robust that no inner core or outer cage is required.



BECO PROTECT KM stainless steel filter cartridges

Stainless steel filter cartridges that are constructed from porous metal powder (316L) predominately used in steam filtration for the separation of rust particles and abraded matter. These cartridges are designed for liquid filtration at high temperatures.



BECO MEMBRAN H Air/H Air Mini membrane filter cartridges

Membrane filter cartridges that retain contaminants up to 0.01 µm and are primarily used for sterile filtration of gases and air. Available in 1", 5", 10", 20" and 30".

ADAPTER CODES



Code X: Double open end (DOE) without end caps



Code F: Double open end (DOE) with two flat gaskets



Code 0: Single open end (SOE), 2-222 O-ring without spear, external diameter 1.57 in (44 mm) (bottom-most point)



Code 2: Single open end (SOE), 2-222 O-ring, triple bayonet-adapter with spear, external diameter 1.57 in (44 mm) (bottom-most point)



Code 7: Single open end (SOE), 2-226 O-ring, double bayonet-adapter with spear, external diameter 2.2 in (56 mm) (bottom-most point)

Technical data

Filter cartridge type	BECO PROTECT PG	BECO PROTECT CS	BECO PROTECT FS	BECO PROTECT PP Pure	BECO PROTECT PB	BECO PROTECT KM
Article number	PG002 – PG995	CS115, CS170, CS270	FS002 – FS200	PPP6 – PPP20	PB005 – PB999	KM10
Filter material	Polypropylene (PP)	Special cellulose	Polypropylene (PP)	Polypropylene (PP)	Polypropylene (PP)	Stainless steel 316L (1.4404)
Retention rating (µm)	0.2, 0.3, 0.5, 0.6, 0.8 1, 2, 3, 5, 10, 15, 20, 30, 40, 50, 75, 100, 120, 150	0.2, 0.4, 0.7	0.2, 0.3, 0.5, 0.6, 0.8 1, 2, 3, 5, 10, 20	0.6, 1.2, 3, 5, 10, 20	0.5, 1, 3, 5, 10, 25 50, 75, 100	10
Retention efficiency	99.98%	Nominal	99.98%	99.98%	90%	Nominal
Lengths	9.75", 10", 19.5", 20", 29.5", 30", 40"	30", 40"	10", 20", 30", 40"	10", 20", 30", 40"	9.75", 10", 19.5", 20", 29.5", 30", 39", 40"	10", 20", 30"
Adapter codes	X, F, 0, 2, 7	2, 7	F, 0, 2, 7	F, 0, 2, 7	X, F	7
Cages	Yes	Yes	Yes	Yes	No	No
Backwashability	Up to 29 psid (2.0 bar) at 176 °F (80 °C)	Up to 29 psid (2.0 bar) at 176 °F (80 °C)	Up to 29 psid (2.0 bar) at 176 °F (80 °C)	Up to 29 psid (2.0 bar) at 68 °F (20 °C)	Yes	Up to 14.5 psid (1.0 bar) at 77 °F (25 °C)
Chemical resistance	pH 1 – 14	Limited	pH 1 – 14	pH 1 – 14	pH 1 – 14	pH 1 – 14
Max. operating temperature	176 °F (80 °C)	176 °F (80 °C)	176 °F (80 °C)	176 °F (80 °C)	149 °F (65 °C)	392 °F (200 °C)
Max. differential pressure in flow direction	69.6 psid (4.8 bar) at 77 °F (25 °C) 29 psid (2.0 bar) at 176 °F (80 °C)	21.8 psid (1.5 bar) at 68 °F (20 °C)	69.6 psid (4.8 bar) at 77 °F (25 °C) 29 psid (2.0 bar) at 176 °F (80 °C)	72.5 psid (5.0 bar) at 68 °F (20 °C) 29 psid (2.0 bar) at 176 °F (80 °C)	46.4 psid (3.2 bar) at 68 °F (20 °C) 17.4 psid (1.2 bar) at 140 °F (60 °C)	–
Steam cycles	> 100 at 230 °F (110 °C) in 30 minutes	> 100 at 230 °F (110 °C) in 30 minutes	> 100 at 230 °F (110 °C) in 30 minutes	> 100 at 230 °F (110 °C) in 30 minutes	Not recommended	n.a.

Filter cartridge type	BECO MEMBRAN PS Beer	BECO MEMBRAN PS Wine	BECO MEMBRAN PS Aqua	BECO MEMBRAN PS Pure	BECO MEMBRAN PPlus	BECO MEMBRAN H Air	BECO MEMBRAN H Air Mini
Article number	PSB04, PSB06	PSW04, PSW06	PSA02	PSP02, PSP04, PSP06, PSP10	KVBB, KVBY, (KVBA)	PTC02	PTM02
Filter material	Polyethersulfone	Polyethersulfone	Polyethersulfone	Polyethersulfone	Polyvinylidene fluoride (PVDF)	Teflon (PTFE)	Teflon (PTFE)
Retention rating (µm)	0.45, 0.65	0.45, 0.65	0.2	0.2, 0.45, 0.65, 1.0	0.22, 0.45, 0.65, (1)	0.2	0.2
LRV (Titer reduction/cm ²)*	>7	>7	>7	>7 1 µm: 6	>7	>7	>7
Lengths	30", 40"	20", 30"	20", 30", 40"	10", 20", 30", 40"	30"	10", 20", 30"	1", 5"
Adapter codes	2, 7	2, 7	2, 7	0, 2, 7	7	7	1, 4, 7
Cages	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Pressure hold test Test pressure in bar and diffusion rate per 10"	PSB04 17.4 psig (1.2 bar) ≤ 15 ml/min PSB06 11.6 psig (0.8 bar) ≤ 5 ml/min	PSW04 21.8 psig (1.5 bar) ≤ 15 ml/min PSW06 14.5 psig (1.0 bar) ≤ 10 ml/min	PSA02 36.3 psig (2.5 bar) ≤ 20 ml/min	PSP02 36.3 psig (2.5 bar) ≤ 20 ml/min PSP04 21.8 psig (1.5 bar) ≤ 15 ml/min PSP06 14.5 psig (1.0 bar) ≤ 10 ml/min PSP10 10.2 psig (0.7 bar) ≤ 15 ml/min	KVBB = 0.45 µm 21.8 psig (1.5 bar) 17.1 ml/min KVBY = 0.65 µm 8.7 psig (0.6 bar) 9.1 ml/min	PTC02 Nitrogen diffusion at 68 °F (20 °C) per 10" ≤ 7 ml/min at 10.3 psig (0.7 bar) with 60% isopropanol	PTM02 Bubble point test at 73 °F (23 °C) ≥ 14.5 psig (1000 mbar) in 60% isopropanol
Backwashability	Limited 29 psid (2.0 bar) at 68 °F (20 °C)	Limited 29 psid (2.0 bar) at 68 °F (20 °C)	Limited 29 psid (2.0 bar) at 68 °F (20 °C)	Limited 29 psid (2.0 bar) at 68 °F (20 °C)	Limited up to 50 psid (3.5 bar) at 77 °F (25 °C)	–	–
Chemical resistance	pH 1 – 14	pH 1 – 14	pH 1 – 14	pH 1 – 14	pH 1 – 12	pH 1 – 14	pH 1 – 14
Max. operating temperature	176 °F (80 °C)	176 °F (80 °C)	176 °F (80 °C)	176 °F (80 °C)	176 °F (80 °C)	176 °F (80 °C)	176 °F (80 °C)
Max. differential pressure in flow direction	72.5 psid (5.0 bar) at 68 °F (20 °C) 4.4 psid (0.3 bar) at 250 °F (121 °C)	72.5 psid (5.0 bar) at 68 °F (20 °C) 4.4 psid (0.3 bar) at 250 °F (121 °C)	72.5 psid (5.0 bar) at 68 °F (20 °C) 4.4 psid (0.3 bar) at 250 °F (121 °C)	72.5 psid (5.0 bar) at 68 °F (20 °C) 4.4 psid (0.3 bar) at 250 °F (121 °C)	72.5 psid (5.0 bar) at 68 °F (20 °C) 4.4 psid (0.3 bar) at 250 °F (121 °C)	72.5 psid (5.0 bar) at 68 °F (20 °C) 7.25 psid (0.5 bar) at 273 °F (134 °C)	72.5 psid (5.0 bar) at 68 °F (20 °C) 7.25 psid (0.5 bar) at 273 °F (134 °C)
Steam cycles	≥ 100 at 221 °F (105 °C) in 30 minutes	≥ 100 at 221 °F (105 °C) in 30 minutes	≥ 100 at 221 °F (105 °C) in 30 minutes	≥ 100 at 221 °F (105 °C) in 30 minutes	≥ 100 at 230 °F (110 °C) in 30 minutes	≥ 150 at 273 °F (134 °C) in 20 minutes	50 at 273 °F (134 °C) in 20 minutes

* Please see technical data sheets for further information about the used test organisms



Application examples

Filtration level	Wine	Beer	Fruit juice	Water	Spirits
Rinsing water filtration (two-level combination possible)	BECO PROTECT PG; FS (0.5 – 10 µm)	BECO PROTECT PG; FS (0.5 – 10 µm)	BECO PROTECT PG; FS (0.5 – 10 µm)	BECO PROTECT PG; FS (0.5 – 10 µm)	BECO PROTECT PG; FS (0.5 – 10 µm)
Particle filtration	BECO PROTECT PG; FS; PP Pure (2 – 5 µm)	BECO PROTECT PG; FS; (5 – 20 µm)	BECO PROTECT PG; FS; (5 – 10 µm)	BECO PROTECT PG; FS; (5 – 10 µm)	BECO PROTECT PG; FS; (5 – 20 µm)
Fine filtration	BECO PROTECT PG; CS; FS; PP Pure (0.5 – 1 µm)	BECO PROTECT PG; CS; FS; (0.5 – 2 µm)	BECO PROTECT PG; FS; PP Pure (0.5 – 1 µm)	BECO PROTECT PG; FS; PP Pure (1 – 3 µm)	BECO PROTECT PG; FS; PP Pure (0.5 – 1 µm)
Membrane protection	BECO PROTECT PG; CS; FS; PP Pure (0.2 – 0.6 µm)	BECO PROTECT PG; FS; (0.3 – 0.6 µm)	BECO PROTECT PG; CS; FS; PP Pure (0.2 – 0.6 µm)	BECO PROTECT PG; FS; PP Pure (0.3 – 1 µm)	–
Membrane filtration	BECO MEMBRAN PS Wine (0.45 – 0.65 µm)	BECO MEMBRAN PS Beer (0.45 – 0.65 µm)	BECO MEMBRAN PS Pure (0.2 – 0.45 µm)	BECO MEMBRAN PS Aqua (0.2 µm)	–
Process water filtration	BECO PROTECT CL (5 – 40 µm)	BECO PROTECT CL (5 – 40 µm)	BECO PROTECT CL (5 – 40 µm)	BECO PROTECT CL (5 – 40 µm)	BECO PROTECT CL (5 – 40 µm)
Rinse water filtration	BECO PROTECT PB (1 – 10 µm)	BECO PROTECT PB (1 – 10 µm)	BECO PROTECT PB (1 – 10 µm)	BECO PROTECT PB (1 – 10 µm)	BECO PROTECT PB (1 – 10 µm)
Steam filtration	BECO PROTECT KM (10 µm)	BECO PROTECT KM (10 µm)	BECO PROTECT KM (10 µm)	BECO PROTECT KM (10 µm)	BECO PROTECT KM (10 µm)
Gas filtration	BECO MEMBRAN H Air; H Air mini (0.2 µm)	BECO MEMBRAN H Air; H Air mini (0.2 µm)	BECO MEMBRAN H Air; H Air mini (0.2 µm)	BECO MEMBRAN H Air; H Air mini (0.2 µm)	BECO MEMBRAN H Air; H Air mini (0.2 µm)

FILTER CARTRIDGE HOUSINGS



BECO INTEGRA CART KA/KB

These filter cartridge housings are manufactured from AISI 316L stainless steel and can be used for the liquid filtration in the food and beverage industry. They are available in 1-, 3-, 5-, 8-, 12-, 18-, 24- and 30-fold cartridge versions for pre-filtration or sterile filtration purposes.



BECO INTEGRA CART KK

These filter cartridge housings are manufactured from AISI 316L stainless steel and designed for pressurized air or steam filtration applications.



BECO INTEGRA CART KLAV

These filter cartridge housings are manufactured from AISI 316L stainless steel and are used as vent filter housings for gas filtration. This series is suitable for sterile filtration for filter cartridges with a code 1 adapter.



BECO INTEGRA CART KLO

These filter cartridge housings are manufactured from AISI 316L stainless steel and are used for pressurized air or steam filtration applications, including emptying and ventilation.

TESTING DEVICES



BECO LiquiControl₂

The BECO LiquiControl₂ index measuring device is used to determine the filterability of any ready-to-bottle beverage. Prior to membrane filtration, a sample is filtered under defined conditions (constant pressure) through a reference membrane.



BECO Control Mini

The BECO Control Mini integrity test unit facilitates the execution of integrity tests for membrane filter cartridges. The extremely precise measurement of the pressure drop in mbar guarantees that the integrity of the membrane filter cartridges is maintained and thus ensures guaranteed microbiological stability.



BECO MAX₂

The fully automatic integrity test unit BECO MAX₂ is designed for the regular testing of membrane filter cartridges, and features an easy-to-use keypad and backlit four-line display in a stainless steel housing.

North America

44 Apple Street
Tinton Falls, NJ 07724
Toll Free: 800 656-3344
(North America only)
Tel: +1 732 212-4700

Europe/Africa/Middle East

Auf der Heide 2
53947 Nettersheim, Germany
Tel: +49 2486 809-0

Friedensstraße 41
68804 Altludersheim, Germany

Tel: +49 6205 2094-0
An den Nahewiesen 24
55450 Langenlonsheim, Germany
Tel: +49 6704 204-0

China

No. 3, Lane 280,
Linhong Road
Changning District, 200335
Shanghai, P.R. China
Tel: +86 21 5200-0099

Singapore

100G Pasir Panjang Road #07-08
Singapore 118523
Tel: +65 6825-1668

Brazil

Av. Ermano Marchetti, 1435 -
Água Branca, São Paulo - SP,
05038-001, Brazil
Tel: +55 11 3616-8461

**For more information, please
email us at filtration@eaton.com
or visit www.eaton.com/filtration**

© 2019 Eaton. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.

US
1 A 4.5
10-2019

