



NOBILI



SDS

Andanatore per pacciamatura

Windrow-maker for mulched stubble



SDS

Per la pacciamatura di vigneti e frutteti inerbiti
For mulched stubble in grassy vineyards and orchards



Il sistema SDS, Side Delivery System, brevettato, è un dispositivo che consente di tritare erba o colture erbacee e di scaricare il materiale tritato in andane simmetriche da entrambi i lati al di sotto delle piante in vigneti e frutteti. Anni di sperimentazione, in collaborazione con l'università di Bologna e Firenze, hanno dimostrato che SDS è un valido strumento per la gestione dei vigneti e dei frutteti, grazie all'alta produttività e alla riduzione dei trattamenti di concimazione e diserbo necessari alle coltivazioni. SDS può appoggiare su rullo o su ruote che ne regolano l'altezza di lavoro ed è dotato di velocità di andatura regolabile per adeguare la portata di biomassa alla velocità del trattore e all'altezza dell'erba. SDS è disponibile nelle versioni con singola e doppia coclea e con circuito idraulico indipendente come optional.

The patented SDS, Side Delivery System, is a device that allows to shred grass or grassy crops and discharge the chopped material in symmetrical windrows on both sides below the plants in vineyards and orchards. Many years of experimentation and cooperation with the Universities of Bologna and Florence, have demonstrated that SDS is a valid instrument for managing vineyards and orchards, thanks to the high productivity and the reduction of fertilizing and weed control treatments necessary to cultivations.

SDS machines are supported by a roller or wheels adjusting their working height and it is possible to control the discharging speed (in windrows) to adequate the biomass rate according to the tractor speed and the grass height. SDS is available with single or double auger and with independent oil tank on option.













Coclee coassiali con spirali opposte per la pacciamatura da ambo i lati.
Coaxial spirals with opposite helices for mulched stubble delivery on both sides.



Coclea singola per la pacciamatura da un solo lato.
Single spiral for mulched stubble delivery on one side.



SDS

Mod.	 mm	Spst. laterale Offset Desplazamiento lateral					 Rotor rpm	N°					 Kg
		mm	mm	HP	KW	rpm				A mm	B mm	C mm	
SDS 120 DOPPIA	1120	560	560	30-95	22-70	540	2230	06		1500	1380	420	410
SDS 120 XL DOPPIA	1120	560	560	30-95	22-70					1800	1380	420	420
SDS 150 MONO	1520	760	760	40-95	29-70			20		1800	1380	420	470
SDS 150 DOPPIA		390	1130							1800	1380	420	470
SDS 180 MONO	1810	760	760	50-110	37-81			24		2100	1380	420	530
SDS 180 DOPPIA		390	1130							2100	1380	420	530
SDS 210 MONO	2100	760	1340	60-110	44-81			28		2380	1380	420	595
SDS 210 DOPPIA		390	1710							2380	1380	420	595
SDS 210 DOPPIA		1050	1050										

Concessionario / dealer:



40062 MOLINELLA (Bologna) - Italy - Tel. +39 051 881444
Fax +39.051.88.27.03 - www.nobili.com - info@nobili.com