



95# White Valencia

Looking for a facestock with substance and old world artisan feel? Perhaps you want to create a contrasting backdrop to your contemporary label design? Then you should consider Valencia with its simple, yet ornate natural emboss pattern appearance. Get the premium look and feel but also feel good about its FSC® certification as an environmentally friendly labelstock. Get the performance you need with our wet strength properties that allow labels to hold up in moist, humid, and wet environments - giving you a durable beverage label.

Celebrating
SURFACES
&
TEXTURES



wausau **coated**

Experts in "What If..."

wausaucoated.com

800-345-8039

WINE & SPIRITS PRODUCT BULLETIN



Experts in "What If..."

95# White Valencia Specialty Label Stock

Wausau Coated Products introduces 95# White Valencia; a specialty facestock that has a simple, yet ornate natural emboss pattern with an artistic stucco appearance. It is manufactured with wet strength properties to increase performance in moist environments and it is FSC® Certified. This label stock features i8017, an ultra-aggressive permanent adhesive designed to deliver ultimate adhesion to a variety of substrates and is water resistant. This chic label stock is a great choice for wine, spirits and craft beverages.

- **W032927 - HP Indigo Optimized 95# White Valencia w/Wet Strength / i8017 / 1.2 mil Clear PET**

For additional product information and to request samples, visit our website at www.wausaucoated.com or contact our Customer Service Department at 800-345-8039.

FACESTOCK DESCRIPTION: INDIGO OPTIMIZED 70# WHITE VALENCIA

Sophisticated white facestock that features a simple, yet ornate natural emboss pattern. It contains wet strength properties. Top coated and optimized for HP Indigo presses.

Basis Weight (25 x 38 /500), lbs.	95
Caliper, mils	7.8
Regulatory Compliances	FSC® Certified

ADHESIVE DESCRIPTION: i8017

i8017 is an ultra-aggressive permanent adhesive designed for difficult-to-label surfaces. It offers excellent initial tack and ultimate adhesion to a variety of substrates. i8017 is UV resistant, water resistant and offers some solvent resistance.

Type	High Performance Acrylic
Classification	Acrylic
Minimum Application Temp °F	+20
Service Temperature Range °F	-20 to +300
Regulatory Compliances	California Prop 65, CONEG, Natural Rubber Latex Free, REACH, RoHS, FDA 21 CFR 175.105, FDA 21 CFR 175.125 Table 2 D-G, FDA 21 CFR 176.180

LINER DESCRIPTION: 1.2 MIL CLEAR PET

A clear polyester film liner with high strength and durability. Typically used for high speed automatic roll-to-roll applications.

Caliper, mils	1.2
Yield, sq. in/lb	16,500
Tensile Strength, MD / TD, psi	29,900 / 29,900
Haze, %	3.5%
Elongation at break, MD / TD %	100 / 100
Shrinkage at 302°F/30 min. MD/TD %	2 / 0.4



Shelf life: One year when stored at 72° F / 50% RH

Note: All product specifications are for informational use only. For more details visit wausaucoated.com